



Tsunami[®] MP-8200 Series

End-to-End Broadband Wireless Product Portfolio

- **Tsunami[®]MP.11** – Our best selling Point-to- Multipoint product line
- **MeshMAX** – An all-in-one solution containing Point-to-Multipoint, Wi-Fi mesh, and Wi-Fi access point radios
- **ORINOCO[®] AP** - The industry's highest performance 802.11a/b/g/n access points
- **Tsunami[®]MP.16** – WiMAX for the 3.3 – 3.65 GHz frequency bands

Proxim Wireless is a global pioneer of end-to-end broadband wireless systems that deliver the quadruple play of video, voice, data and mobility. From Wi-Fi to wireless Gigabit Ethernet – our WLAN, Wi-Fi Mesh, WiMAX and point-to-point wireless backhaul products are available through our extensive global channel networks.

Experience superior performance with unparalleled flexibility of upto 1 Mhz channel spacing with our Tsunami[®] MP-8200 wireless series

Paving a new path in the wireless industry, Proxim addresses the requirement for a versatile and a high performance wireless solution, with the Tsunami[®] 8200 series. The Tsunami[®] MP-8200 delivers data rates of 300 Mbps along with excellent spectrum flexibility of upto 1MHz channel spacing and high power radios capable of 27 dBm Tx power for extend coverage.

The Tsunami[®] MP-8200 features nLoS functionality and leverages the advantages of OFDM, MIMO radio innovations and Proxim's proprietary Wireless Outdoor Routing Protocol (WORP) to provide in excess of 4G speeds with QoS class of service for delivering voice, video and data applications

With supreme throughput, high power radio, flexible channel features and dual Gigabit Ethernet ports with PoE out, for powering additional devices, the Tsunami[®] MP-8200 series is an ideal solution for service providers and government organizations with requirements of all kinds, from last mile broadband wireless access (BWA) to wireless video surveillance and more.

Supreme Performance

- A fixed PtMP solution that can deliver 300 Mbps data rates
- High power radio capable of up to 27 dBm Tx power to extend the range and coverage
- The only PtMP product in the market to include dual Gigabit Ethernet ports, enabling higher throughput which would otherwise be limited by the 10/100 Ethernet ports seen in other devices
- Provides reliable high performance under all traffic loads using Proxim's Wireless Outdoor Routing Protocol (WORP)

Non-Line-of-Sight and Advanced Features

- Non-line-of-sight capable, utilizing OFDM and 2x2 MIMO techniques to improve link performance and penetrate through or around obstructions better
- Features dual Gigabit Ethernet ports with PoE in/out to power other devices like surveillance cameras and wireless access points
- Create tiered QoS service classes with ease

Frequency Agnostic

- Operates in licensed and unlicensed frequency bands
- Flexible channel planning with 5, 10, 20 and 40MHz support with 1MHz channel spacing
- Provides support for extended frequency bands from 4.9 to 5.9 GHz

Carrier-Grade Security

- Implements tiered security layers for the most secure outdoor wireless communications in the unlicensed frequency spectrum
- Utilizes Proxim's Wireless Outdoor Routing Protocol (WORP), which prevents snooping, and features highly-secure remote management via SSL, SSH and SNMPv3
- Provides military-grade security with AES encryption technology, prevents unsecure client-to-client communications and leverages MAC, Ethertype and IP address packet filtering for granular network security

Product Line Compatibility

- Connects to all existing Tsunami[®] MP.11, Tsunami[®] 8100, and MeshMAX products
- Can utilize existing mounting kits of the Tsunami product line

PRODUCT MODELS					
MP-8200-BSU	Tsunami® MP 8200 Base Station Unit, 300 Mbps, MIMO 2x2, Type-N Connectors				
MP-8200-SUA	Tsunami® MP 8200 Subscriber Unit, 300 Mbps, MIMO 2x2, Type-N Connectors				
INTERFACES					
WIRED ETHERNET	Two auto MDI-X RJ45 10/100/1000Mbps Ethernet - Port #1 with PoE in & Data - Port #2 with PoE out (802.3af pin out) & Data				
WIRELESS PROTOCOL	WORP (Wireless Outdoor Router Protocol)				
RADIO & TX SPECS					
MIMO	2x2 MIMO				
MODULATION	OFDM				
FREQUENCY	US version : 4.940 – 4.990 and 5.725 – 5.850 GHz World version: 4.900 – 5.925 GHz without DFS support (Subject to Country Regulations)				
CHANNEL SIZE	40 MHz, 20 MHz, 10 MHz, 5MHz channel bandwidths with support for 1MHz channel spacing				
DATA RATE	MCS 0 to 15 for High Throughput mode (6.5 – 300 Mbps) with Dynamic Data Rate Selection BPSK, QPSK, 16-QAM and 64-QAM for legacy mode (6Mbps - 54Mbps)				
TX POWER	Up to 27 dBm (two Tx chain)				
TX POWER CONTROL	0 – 25 dB, in 0.5 dB steps. Automatic TPC with configurable EIRP limit				
RX SENSITIVITY (BER=10 ⁻⁶)	Channel Size	40 MHz	20 MHz	10 MHz	5 MHz
	MCS 0	-87 dBm	-91 dBm	-93 dBm	-96 dBm
	MCS 7	-69 dBm	-72 dBm	-74 dBm	-76 dBm
	MCS 8	-86 dBm	-89 dBm	-91 dBm	-94 dBm
	MCS 15	-67 dBm	-69 dBm	-72 dBm	-74 dBm
ANTENNA	Model MP-8200-BSU and MP-8200-SUA include two N-type Connectors with built-in Surge Protection				
MANAGEMENT					
LOCAL	RS-232 serial (RJ11 to DB-9 dongle provided)				
REMOTE	Telnet and SSH, WebGUI and SSL, TFTP, SNMPv3				
SNMP	SNMP v1-v2c-v3, RFC-1213, RFC-1215, RFC-2790, RFC-2571, RFC-3412, RFC-3414, Private MIB				
OTHER	Syslog, sFlow™ agent, SNTP and local time				
SECURITY					
ENCRYPTION	AES-CCM 128 bits				
AUTHENTICATION	Internal MAC Address Control List, Radius based Authentication (with VLAN and QoS provisioning)				
NETWORK					
MODES	Bridging, Routing (RIP v2 and IP tunneling)				
GATEWAY FEATURES	DHCP Server & relay, NAT with Std ALGs, PPPoE end point				
QoS	Asymmetric Bandwidth Control	Uplink and Downlink CIR Control "committed information rate" per service flow Uplink and Downlink MIR Control "maximum information rate" per service flow			
	Packet Classification Capabilities	802.1D/802.1Q/802.1p priority, IPTOS, VLAN ID, IP source/destination address, source/destination port, Ethernet source/destination address, IP protocol, and Ethertype			
	Scheduling	Best Effort, Real Time Polling Services			
VLAN	802.1Q: Management VLAN. Transparent, Access, Trunk and Mixed mode. QinQ double tagging				
ENVIRONMENTAL SPECS					
TEMPERATURE					
OPERATING	-40° to 60°C (-40° to 140° Fahrenheit)				
STORAGE	-55° to 80°C (-67° to 176° Fahrenheit)				
HUMIDITY	Max 100% relative humidity (non-condensing)				
IP RATING	IP67				
WIND LOADING	125 mph				
POWER CONSUMPTION	8.1 Watt typical (18.1 Watt max)				
PHYSICAL SPECS					
DIMENSIONS					
PACKAGED	Model MP-8200-BSU or MP-8200-SUA: 14.56 x 13.69 x 8.18 in. (370 x 348 x 208 mm)				
UNPACKAGED	Model MP-8200-BSU or MP-8200-SUA: 10.5 x 10.5 x 3.38 in (267 x 267 x 86 mm)				
WEIGHT					
PACKAGED	Model MP-8200-BSU or MP-8200-SUA: 16.75 lbs (7.6 kg)				
UNPACKAGED	Model MP-8200-BSU or MP-8200-SUA: 7.27 lbs (3.3 kg)				
SAFETY STANDARDS					
PACKAGE CONTENTS					
<ul style="list-style-type: none"> ■ One Tsunami® MP 8200-BSU with two N-type surge protected connectors, or One Tsunami® MP 8200-SUA with two N-type surge protected connectors, ■ One power injector and country specific power cord ■ One Wall/Pole mounting kit ■ One Connector weatherproofing kit (Includes all recommended weatherproofing material) ■ One Serial (RJ-11 to DB9) dongle ■ One Grounding kit ■ One Gigabit PoE Surge Arrester ■ One Quick Installation Guide 					
WARRANTY					
1-year on parts and labor; ServPak Extended Support available					

APPLICATIONS

- Last Mile Access**
 Competitive broadband service access alternative to DSL or cable for residences and T1 or Ethernet for businesses
- Security and Surveillance**
 High definition IP-surveillance cameras for monitoring city streets, airports, bridges, seaports, transportation hubs, offices and warehouses
- Metropolitan Area Networks**
 Secure and reliable connectivity between city buildings
- Emergency First Responders**
 Critical information delivery such as medical data and video feeds during in-progress events
- Enterprise Campus Connectivity**
 Extend the main network to remote offices, warehouses or other buildings without leased lines

For detailed technical specifications, please go to <http://proxim.com/products/point-to-multipoint/tsunamir-mp-8200-series>

©2012 Proxim Wireless Corporation. All rights reserved. Proxim is a registered trademark and the Proxim logo and Tsunami® are trademarks of Proxim Wireless Corporation. All other trademarks mentioned herein are property of their respective owners. Specifications are subject to change without notice.