



Bandwidth licensed to support 50, 100 and 200 Mbps throughput options.

The Quickbridge[®] 10100-xxx, is a compact bandwidth controlled version of the Quickbridge[®] 10100 product family, and offers all the advanced features and benefits of the 10100 series with lower cost of entry. The ability to scale the bandwidth from 50 to 200 Mbps as needed allows the network designer to right-size the link to suit the needs of the application.

This highly reliable and compact product is ideal for installation in cities and by major highways, where wireless point-to-point networks provide the best and lowest cost backhaul of video, radar and traffic control data.

The Quickbridge[®] 10100 supports the following key features that are critical for carriers, wireless service providers and Government organizations that need to know they can rely on the network.

Rugged and Reliable

Designed for harsh environments, the QuickBridge[®] 10100 is fully IP67 rated, and will deliver years of reliable service in conditions that include, high winds, high salt, and high temperature extremes.

Highlights

- Service flow based QoS with deep packet inspection (DPI) to ensure that the most important data arrives with priority
- Very low latency enables support for time critical applications
- Operates in unlicensed bands from 4.900 to 5.925 GHz
- Flexible RF planning with 20, 40 and 80 MHz channel size
- Non Line-of-Sight capability provided by Advanced Orthogonal Frequency Division Multiplexing (OFDM) along with 2x2 MIMO eases deployment in challenging areas
- Deployment tools include spectrum analyzer, antenna alignment and remote management configuration
- Fully integrates within ProximVision[®] Advanced Carrier Management System.

Enabling Technologies

Proxim WORP[®]

Combines network access control, data scheduling, advanced QoS and encryption to ensure highly efficient and secure data transmission.

Proxim ClearConnect[™]

A suite of interference mitigation technologies ensuring robust and reliable communications in high-density wireless deployments.

Multi-Language Support

Web Interface available in English, French, Spanish and Chinese

About Proxim Wireless

Proxim Wireless is a pioneer and global leader in advanced Wi-Fi, point to point, and point to multipoint outdoor wireless systems that deliver high performance and high availability communications.

With over 30 years of wireless experience, Proxim is recognized for its unparalleled reliability, superior performance and drive for innovation.

Specifications

PRODUCT MODELS		PART NUMBERS	
QB-10100-LNK-50	Tsunami QB 10100 Link, 50 Mbps, MIMO 2x2, Type-N Connectors (two QB-10100-EPA-50)	902-00847 QB-10100-LNK-50-US 902-00849 QB-10100-LNK-50-WD	
QB-10100-LNK-100	Tsunami QB 10100 Link, 100 Mbps, MIMO 2x2, Type-N Connectors (two QB-10100-EPA-100)	902-00851 QB-10100-LNK-100-US 902-00853 QB-10100-LNK-100-WD	
LICENSE UPGRADE			
QB-10100-LNK-100-UPG	Tsunami QB 10100 Link, 50 Mbps to 100 Mbps license upgrade Part Number : 997-00038		
QB-10100-LNK-200-UPG	Tsunami QB 10100 Link, 100 Mbps to 200 Mbps license upgrade Part Number : 997-00039		
INTERFACES			
WIRED ETHERNET WIRELESS PROTOCOL	One auto MDI-X RJ45 10/100/1000Mbps Ethernet with PoE in WORP® (Wireless Outdoor Router Protocol)		
RADIO & TX SPECS			
MIMO	2x2:2		
MODULATION	OFDM with BPSK, QPSK, QAM16, QAM64, QAM256		
FREQUENCY	4.900 – 5.925 GHz (Subject to Country Regulations)		
CHANNEL SIZE	80 MHz, 40 MHz and 20 MHz (±5ppm channel accuracy)		
DATA RATE	MCS 0 to 9 with Dynamic Data Rate Selection		
TX POWER	Up to 28 dBm (dual chain)		
TX POWER CONTROL	0 - 27 dB, in 1 dB steps. Automatic TPC with configurable EIRP limit		
	80 MHz	40 MHz	20 MHz
TX POWER (dual RF)	MCS0: 28 MCS9: 21	MCS0: 28 MCS9: 22	MCS0: 29 MCS8: 25
RX SENSITIVITY (Per=10%)	MCS0: -89 MCS9: -68	MCS0: -93 MCS9: -71	MCS0: -94 MCS8: -74
THROUGHPUT	License controlled to 50, 100 or 200 Mbps		
OTHER	Dynamic Channel Selection (DCS) based on interference detection, Dynamic Frequency Selection (DFS) based on radar signature, Automatic Transmit Power Control (ATPC) with EIRP limit support		
ANTENNA			
QB-10100-EPA	Two N-type Connectors		
MANAGEMENT			
REMOTE SNMP OTHER Multi-Language Support	Telnet and SSH, Web GUI and SSL, TFTP, SNMPv3 SNMP v1-v2c-v3, RFC-1213, RFC-1215, RFC-2790, RFC-2571, RFC-3412, RFC-3414, Private MIB Syslog, sFlow™ agent, SNMP and local time, Spectrum analyzer Web Interface available in English, French, Spanish and Chinese		
SYNCHRONIZATION			
	Pass-through SyncE and Precision Time Protocol (IEEE 1588v2) Ethernet Synchronization		
SECURITY			
ENCRYPTION AUTHENTICATION	AES 128 Internal MAC Address Control List, Radius based Authentication (with VLAN and QoS provisioning)		
QoS			
Asymmetric Bandwidth Control Packet Classification Capabilities Scheduling	Asymmetric UL/DL committed and maximum information rate per service flow 802.1p priority, IPTOS, VLAN ID, IP addresses, ports, Ethernet addresses, IP protocol, and EtherType Best Effort, Real Time Polling Services		
NETWORK			
MODES IP STACK GATEWAY FEATURES VLAN	Bridging, Routing (RIP v2 and IP tunneling) IPv4 and IPv6 simultaneously DHCP Server & relay, NAT with Std ALGs, PPPoE end point with Proxy DNS 802.1Q: Management VLAN. Transparent, Access, Trunk and Mixed mode. QinQ double tagging		
POWER SUPPLY			
	36 to 57 VDC via Ethernet port (Power over Ethernet) 12 VDC via Access port Power should not be provided simultaneously on both ports.		
POWER CONSUMPTION			
	11.5 Watt typical, 15.5 Watt maximum		

ENVIRONMENTAL SPECS	OPERATING TEMPERATURE	STORAGE TEMPERATURE	HUMIDITY - IP RATING	WIND LOADING
	-40° to 60°C (-40° to 140° Fahrenheit)	-50° to 70°C (-58° to 158° Fahrenheit)	100% relative humidity - IP67	180 km/h (112.5 mph)
PHYSICAL SPECS	DIMENSIONS PACKAGED	DIMENSIONS UNPACKAGED	WEIGHT (PACKAGED)	WEIGHT (UNPACKAGED)
QB-10100-EPA	11.81x10.83x5.31 in (300x275x135 mm)	5.02x8.68x2.85 in (127.5x220.5x72.5 mm)	6.39 lbs (2.9 kg)	2.75 lbs (1.250 kg)
SAFETY STANDARDS				
	UL 60950, CAN/CSA-C22.2 No. 60950, IEC 60950, EN 60950 (part -1 and -22)			
CERTIFICATIONS				
	USA: FCC 90Y + 15E (UNII 15.247), Canada: IC RSS 102 + RSS 111 + RSS 247 Europe: RED EN 301 489-1 + EN 301-489-17 + EN 301 893 + EN 302 502			
PACKAGE CONTENTS				
	<ul style="list-style-type: none"> • One Tsunami® QB-10100-LNK with two N-type connectors (Two QB-10100-EPA) • Two power injector and country specific power cord • Two Connector weatherproofing kit (Includes all recommended weatherproofing material) • Two Pole mounting kit • Two Grounding kit • Two Quick Installation Guide 			
MTBF & WARRANTY				
	MTBF over 250 000 hours & 2-year warranty with ServPak Extended Support available.			