



Fast and Flexible Backhaul Solutions

The Tsunami Quickbridge® 10100 series delivers high bandwidth backhaul with carrier class reliability in even the toughest of conditions.

Perfectly suited for the service provider or enterprise that needs to connect critical applications and services to the data center or the world.

The range of high-power, integrated and external antenna models provide the flexibility to design a backhaul link that will meet the most stringent criteria.

The Tsunami® Quickbridge® 10100 supports the following key features that are critical for carriers, wireless service providers and Government organizations that need to know they can rely on the network.

Rugged and Reliable

Designed for harsh environments, the Tsunami® QuickBridge® 10100 is fully IP67 rated, and will deliver years of reliable service in conditions that include, high winds, high salt, and high temperature extremes.

Highlights

- Service flow based QoS with deep packet inspection (DPI) to ensure that the most important data arrives with priority
- Very low latency enables support for time critical applications
- Operates in unlicensed bands from 4.900 to 5.925 GHz
- Flexible RF planning with 20, 40 and 80 MHz channel size
- Non Line-of-Sight capability provided by Advanced Orthogonal Frequency Division Multiplexing (OFDM) along with 2x2 MIMO eases deployment in challenging areas
- Deployment tools include spectrum analyzer, antenna alignment and remote management configuration
- Fully integrates within ProximVision® Advanced Carrier Management System.

Enabling Technologies

Proxim WORM®

Combines network access control, data scheduling, advanced QoS and encryption to ensure highly efficient and secure data transmission.

Proxim ClearConnect™

A suite of interference mitigation technologies ensuring robust and reliable communications in high-density wireless deployments.

About Proxim Wireless

Proxim Wireless is a pioneer and global leader in advanced Wi-Fi, point to point, and point to multipoint outdoor wireless systems that deliver high performance and high availability communications.

With over 30 years of wireless experience, Proxim is recognized for its unparalleled reliability, superior performance and drive for innovation.

Specifications

PRODUCT MODELS		PART NUMBERS	
QB-10100-LNK	Tsunami® QB 10100 Link, single radio, 866 Mbps, MIMO 2x2, Type-N Connectors	902-00769	QB-10100-LNK-US
QB-10150-LNK	Tsunami® QB 10150 Link, single radio, 866 Mbps, MIMO 2x2, 22 dBi antenna	902-00771	QB-10100-LNK-WD
QB-10150-LKL	Tsunami® QB 10150 Link Long-range, single radio, 866 Mbps, MIMO 2x2, 28 dBi antenna	902-00773	QB-10150-LNK-US
		902-00775	QB-10150-LNK-WD
		902-00779	QB-10150-LKL-US
		902-00780	QB-10150-LKL-WD
INTERFACES			
WIRED ETHERNET	Two auto MDI-X RJ45 10/100/1000Mbps Ethernet (Port #1 with PoE in & Data, Port #2 with PoE out & Data)		
WIRELESS PROTOCOL	WORP® (Wireless Outdoor Router Protocol)		
RADIO & TX SPECS			
MIMO	2x2:2		
MODULATION	OFDM with BPSK, QPSK, QAM16, QAM64, QAM256		
FREQUENCY	4.900 – 5.925 GHz (Subject to Country Regulations)		
CHANNEL SIZE	80 MHz, 40 MHz and 20 MHz (±5ppm channel accuracy)		
DATA RATE	MCS 0 to 9 with Dynamic Data Rate Selection		
TX POWER	Up to 28 dBm (dual chain)		
TX POWER CONTROL	0 - 27 dB, in 1 dB steps. Automatic TPC with configurable EIRP limit		
	80 MHz	40 MHz	20 MHz
TX POWER	MCS0: 28	MCS0: 28	MCS0: 29
	MCS9: 21	MCS9: 22	MCS8: 25
RX SENSITIVITY (Per=10%)	MCS0: -89	MCS0: -93	MCS0: -94
	MCS9: -68	MCS9: -71	MCS8: -74
THROUGHPUT	Up to 633 Mbps	Up to 324 Mbps	Up to 137 Mbps
OTHER	Dynamic Channel Selection (DCS) based on interference detection, Dynamic Frequency Selection (DFS) based on radar signature Automatic Transmit Power Control (ATPC) with EIRP limit support		
ANTENNA			
QB-10100-EPA	Two N-type Connectors with built-in Surge Protection		
QB-10150-EPR	Integrated 2x2 MIMO 22dBi Dual Polarized 1 foot Panel Antenna		
QB-10150-EPL	Integrated 2x2 MIMO 28dBi Dual Polarized 2 feet Panel Antenna		
MANAGEMENT			
REMOTE	Telnet and SSH, Web GUI and SSL/TLS, TFTP, SNMPv3		
SNMP	SNMP v1-v2c-v3, RFC-1213, RFC-1215, RFC-2790, RFC-2571, RFC-3412, RFC-3414, Private MIB		
OTHER	Syslog, sFlow™ agent, SNTp and local time, Spectrum analyzer		
SYNCHRONIZATION			
	Pass-through IEEE 1588v2 Ethernet Synchronization		
SECURITY			
ENCRYPTION	AES 128		
AUTHENTICATION	Internal MAC Address Control List, Radius based Authentication (with VLAN and QoS provisioning)		
QoS			
Asymmetric Bandwidth Control	Asymmetric UL/DL committed and maximum information rate per service flow		
Packet Classification	802.1p priority, IPTOS, VLAN ID, IP addresses, ports, Ethernet addresses, IP protocol, and EtherType		
Capabilities			
Scheduling	Best Effort, Real Time Polling Services		
NETWORK			
MODES	Bridging (support LACP through external switches), Routing (RIP v2 and IP tunneling)		
IP STACK	IPv4 and IPv6 simultaneously		
GATEWAY FEATURES	DHCP Server & relay, NAT with Std ALGs, PPPoE end point with Proxy DNS		
VLAN	802.1Q: Management VLAN. Transparent, Access, Trunk and Mixed mode. QinQ double tagging		
POWER		INPUT	OUTPUT
		36 to 57 VDC via Ethernet port1 (Power over Ethernet) 12 VDC via Access port Power should not be provided simultaneously on both ports	48 to 57 VDC – 25 Watt on Ethernet port2 (PoE – software controlled) 12 VDC on Access port
POWER CONSUMPTION			
	14 Watt typical, 17.5 Watt maximum		

ENVIRONMENTAL SPECS	OPERATING TEMPERATURE	STORAGE TEMPERATURE	HUMIDITY - IP RATING	WIND LOADING
	-40° to 60°C (-40° to 140° Fahrenheit)	-50° to 70°C (-58° to 158° Fahrenheit)	100% relative humidity - IP67	QB-101x0-EPA/EPR - 200 km/h (125 mph) QB-10150-EPL - 180 km/h (112.5 mph)
PHYSICAL SPECS	DIMENSIONS PACKAGED	DIMENSIONS UNPACKAGED	WEIGHT (PACKAGED)	WEIGHT (UNPACKAGED)
QB-10100-EPA	14.56 x 13.0 x 7.87 in (370 x 331 x 200 mm)	9.84 x 8.66 x 2.83 in (250 x 220 x 72 mm)	9.92 lbs (4.5 kg)	4.20 lbs (1.9 kg)
QB-10150-EPR	14.56 x 13.0 x 7.87 in (370 x 331 x 200 mm)	12 x 12 x 3.40 in (305 x 305 x 85 mm)	10.91 lbs (4.95 kg)	5.30 lbs (2.4 kg)
QB-10150-EPL	27.55 x 6.85 x 27.55 in (700 x 174 x 700 mm)	23.62 x 23.62 x 3.85 in (600 x 600 x 92 mm)	23.15 lbs (10.5 kg)	14.33 lbs (6.5 kg)
SAFETY STANDARDS				
	UL 60950, CAN/CSA-C22.2 No. 60950, IEC 60950, EN 60950 (part -1 and -22)			
CERTIFICATIONS				
	USA: FCC 90Y + 15E (UNII 15.247), Canada: IC RSS 102 + RSS 111 + RSS 247 Europe: RED EN 301 489-1 + EN 301-489-17 + EN 301 893 + EN 302 502			
PACKAGE CONTENTS				
	<ul style="list-style-type: none"> • One Tsunami® QB-10100-LNK with two N-type surge protected connectors (Two QB-10100-EPA) Or One Tsunami® QB-10150-LNK with integrated 22 dBi dual polarized antenna (Two QB-10150-EPR) Or One Tsunami® QB-10150-LKL with integrated 28 dBi dual polarized antenna (Two QB-10150-EPL) • Two power injector and country specific power cord • Two Connector weatherproofing kit (Includes all recommended weatherproofing material) • Two Wall / Pole mounting kit • Two Antenna alignment (RJ11) dongle • Two Grounding kit • Two Quick Installation Guide 			
MTBF & WARRANTY				
	MTBF over 250 000 hours & 2-year warranty with ServPak Extended Support available.			